

# SCPV - TEMPEST Pluggable Filter -13A2S

Silicon CPV's 2 socket, TEMPEST pluggable filter has been designed for use within stringent TEMPEST environments and applications, where protection compliant to SDIP-29 and equipment hardening to SDIP-27 is required.

The product uses ultra-reliable self-healing capacitors, in all units to deliver optimum performance across the full frequency range and under all loading conditions.

The SCPV filter has been designed for use within unprotected power environments to ensure deployment and electrical installation is as quick and simple as possible.

The product has been designed to support current ratings of 13 Amps under single phase operating voltage conditions.




## Description

- TEMPEST EMI SP & N filter providing performance to SDIP-27 B/C
- Insertion loss of 60dB from 100kHz to 1GHz
- **13A BS1363 3 pin plug input** & 2 socket outlets
- Designed to IT equipment safety standard IEC 62368-1:2023
- Fully 360° screened input cable to maintain red/black separation to filter
- Low Smoke Zero Halogen (LSZH) rated cabling for use in sensitive areas
- Self-healing metallised plastic film capacitors
- High common & differential mode insertion loss
- Improved low frequency performance
- Powder coated aluminium enclosure
- 13A designs of filter are downline tolerable to a personnel protection RCCD
- UKCA - CE compliant – Input voltage range (90-275VAC)
- Simple mechanical and electrical installation
- Filters comply with basic requirements of the EMC directive 2014/30/EU


## Ratings and Characteristics

Rated Voltage	230V AC 50/60Hz	Storage Temp Range	-25°C to 85°C
Test Voltage (line-earth)	2250V DC	Operating Temp Range	-20°C to 50°C
Test Voltage (line-Line)	1250V DC	Insertion Loss (50Ω Asymmetric)	60dB, 100KHz - 1GHz
Rated Current @50°C	13A	Discharge Time	Less than 1s to below 34V
Earth Leakage Current	Less than 3.0mA	Enclosure	Extruded Aluminium
Max Temp Rise @Full Load	<35°C	Finish	Powder coated

## Dimensional Data



## Performance Characteristics and Insertion Loss Curves



## Part No and Ordering Information

Part No	Product Description
SCPV – TEMPEST – 13A2S CP&F Part No: SCPVTEMPEST13A2S NATO NO: 5915-99-217-3439	2 x BS1363 Sockets, Maximum 13A Single Phase 230V Pluggable Tempest Filter