



# SCPV - TEMPEST Pluggable Filter – 16A4S – EU

Silicon CPV's 4 socket, TEMPEST pluggable filter has been designed for use within stringent TEMPEST environments and applications, where protection compliant to SDIP-29 and equipment hardening to SDIP-27 is required.

The product uses ultra-reliable self-healing capacitors, in all units to deliver optimum performance across the full frequency range and under all loading conditions.

The SCPV filter has been designed for use within unprotected power environments to ensure deployment and electrical installation is as quick and simple as possible.

The product has been designed to support current ratings of 16 Amps under single phase operating voltage conditions.



#### Description

- TEMPEST EMI SP & N filter providing performance to SDIP-27 B/C
- Insertion loss of 60dB from 100kHz to 1GHz
- 16A Type F plug input & 4 x sockets outlets
- Designed to IT equipment safety standard IEC 62368-1:2023
- Fully 360° screened input cable to maintain red/black separation to filter
- Low Smoke Zero Halogen (LSZH) rated cabling for use in sensitive areas
- Self-healing metallised plastic film capacitors
- High common & differential mode insertion loss
- Improved low frequency performance
- Powder coated aluminium enclosure
- 16A designs of filter are downline tolerable to a personnel protection RCCD
- CE compliant Input voltage range (90-275VAC)
- Simple mechanical and electrical installation
- Filters comply with basic requirements of the EMC directive 2014/30/EU







## **Ratings and Characteristics**

Rated Voltage	230V AC 50/60Hz		Storage Temp Range	-25°C to 85°C
Test Voltage (line-	2250V DC		Operating Temp	-20°C to 50°C
earth)			Range	
Test Voltage (line-Line)	1250V DC		Insertion Loss (50Ω Asymmetric)	60dB, 100KHz - 1GHz
Rated Current @50°C	16A		Discharge Time	Less than 1s to below34V
Earth Leakage Current	Less than 3.0mA		Enclosure	Extruded Aluminium
Max Temp Rise @Full	<35°C		Finish	Powder
Load				coated

## **Dimensional Data**



## **Performance Characteristics and Insertion Loss Curves**



#### Part No and Ordering Information

Part No	Product Description	
SCPV – TEMPEST – 16A4S – EU	4 x Type F Sockets, Maximum16A	
CP&F Part No: SCPVTEMPEST16A4SEU	Single Phase 230V Pluggable	
	Tempest Filter	