

SOLAR LED STREET LIGHTING

City Range

Wireless Remote Monitoring and Control
Easy Installation, Long Service Life, Cost Effective

Multiple Benefits of Silicon CPV Solar Powered Street Lights:

- Ultra-modern design.
- Uses free electricity from the sun so environmentally-friendly and pollution-free
- Easily Replaceable Battery bank housed in a strong aluminum removable cartridge
- Lightweight – each unit is less than 25kg
- Easy to install and safe to use
- Computer-controlled EMS
- No costly or complicated pipe-laying or underground wiring required
- No cabling required
- One unit so no separate battery
- Solar panel 25-year service life
- Special chemistry lithium - ion battery designed for greater than 10-year service life in elevated temperatures
- Remote connectivity
- Stylish and integrated design
- Suitable for 6, 8 and 10meter height poles

No Power Bills, No Grid Connection GSM or Internet based Remote management

Our vision is simple – to develop and manufacture advanced Solar LED Street Lighting systems that will greatly reduce the cost of generating clean electricity from the sun's energy.

Silicon CPV's solar powered street lights are the most economic, reliable and versatile means of providing street lighting.

With a high efficiency long-life light source of up to 550,000 hours, the self-contained units are not only lightweight (less than 25kg per unit) but require no special tools or heavy lifting equipment to install. In fact, they literally take just five minutes to install!



The economic advantage of solar lighting is very clear – deploying a solar light requires no timely and often costly overhead or underground electrical wiring. Further, not having to provide additional electricity from the grid for lighting avoids the incredible expense of power plants and electrical distribution equipment.

The self-contained unit simply converts sunlight during the daytime into electricity and stores it into the battery. After sunset, the solar panel will detect a drop in ambient light and the system will automatically turn on the light. The LED light source complete with integrated lens ensures that all light produced is directed along the road exactly where required.

Silicon CPVs street Lights offer many advantages:

- Solar lighting can save the large amounts of money by eliminating trenching, wiring, electricity cost and ensures that there are few or no landscaping issues.
- Compared to traditional grid-tied lighting, the solar LED lights do not require timers and their LED fixtures do not need regular maintenance visits. In more remote places, solar lights are also a way to help prevent theft.
- Solar lights are good for the environment. Using only the limitless clean energy from the



**Call us today on
+44 (0) 1279 821200
and speak with one of our
sales representatives for
further information.**



Silicon CPV Ltd,

Akhter House, Perry Road, Harlow,
Essex CM18 7PN, UK



+44 (0) 1279 821200



sales@siliconcpv.com

Specifications	City 6	City 8	City 10
Maximum Light Output ((Lumens) Phase 1	5,300	10,600	16,000
Total Light Output ((Lumen Hours) @40% DoD	39,045	78,090	117,135
Battery - Type	Lithium – ion		
Battery Capacity (Wh)	476	952	1,428
Battery - Service Life	10 Years at 40% DoD and at 45° ambient		
Light Source - Type	High Efficiency LED, 5000K Colour Temperature		
Number of LEDs	64	128	192
Light Head Lifetime	80,000 to LM80 specifications		
LED Efficiency	200 lumens / Watt, Colour Temperature 5000K		
Optical Efficiency	>93%		
Solar Panel (W)	194W	388W	582W
Solar Cells	Very High Efficiency – Proprietary Solar Cells (Greater than 20%)		
Solar Panel - Service Life	25 Years		
Controller	Microprocessor based Energy Management and Wireless Communications		
Wireless Network	Proprietary Wireless Network allows Remote Management and Control of Lights using Internet or GSM. One gateway per 100 lights and all the gateways report to a central control room.		
Light Control	Intelligent Adaptive Light level control based on energy received or a predefined light level option is user selectable		
Light Hours	Programmable trigger levels from "Dusk to Dawn"		
Optics	8 different light profiles available for each light		
Recommended Pole Height	6 m	8 m	10 m
Pole Spacing	5 times Pole height for T2 Optics (IESNA Type II)		
Average Light level (Lux) with T2 Optics	20	22	21
Dimensions (L x W) mm (Provisional)	2000 x 100	2000 x 100	2000 x 100
Weight (Kg) (Provisional)	25kg	25kg	25kg
Operating Temperature	-20°C to +60°C		
Protection Rating	IP66		
Standards Compliance	BS 5489:2003 EN13201, ME4a, IESNA Type II or Type III		