

# SCPV12-10 (12V10Ah)

SCPV12-10 is a general purpose battery with 5 years floating design life, meet with IEC, JIS standard .With heavy duty grid, thickness plates, special additives, RT series battery have long and reliable standby service life.




## Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	10Ah@20hr-rate to 1.75V per cell @25°C
Weight	Approx. 3.10 Kg
Max. Discharge Current	100 A (5 sec)
Internal Resistance	Approx. 18 mΩ
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C±5°C
Float charging Voltage	13.7 to 13.9 VDC/unit Average at 25°C
Recommended Maximum Charging Current Limit	3 A
Equalization and Cycle Service	14.6 to 14.8 VDC/unit Average at 25°C
Self Discharge	Silicon CPV Valve Regulated Lead Acid (VRLA) batteries can be stored for more than 6 months at 25°C. Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Terminal	Faston Tab 187(F1)/Faston tab 250(F2)
Constainer Material	A.B.S. (UL94-HB) , Flammability resistance of UL94-V2 can be available upon request.



## Dimensions

Unit: mm Dimension: 151(L)×98(W)×101(H)



## Constant Current Discharge Characteristics : A(25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	40.66	26.66	20.90	11.73	6.970	4.014	2.728	2.183	1.813	1.155	1.000	0.561
10.0V	39.19	25.99	20.23	11.58	6.780	3.933	2.678	2.153	1.782	1.150	0.989	0.541
10.2V	36.89	24.71	19.66	11.40	6.716	3.892	2.654	2.132	1.763	1.140	0.974	0.531
10.5V	33.16	23.10	18.55	11.09	6.584	3.841	2.630	2.111	1.742	1.129	0.969	0.515
10.8V	29.71	21.54	17.50	10.72	6.465	3.809	2.599	2.101	1.723	1.125	0.953	0.485
11.1V	25.99	19.75	16.14	10.31	6.292	3.656	2.549	2.082	1.706	1.116	0.938	0.477

## Constant Power Discharge Characteristics : W(25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	427.8	283.6	223.7	134.3	80.93	46.83	31.89	25.83	21.46	13.83	11.98	6.724
10.0V	416.6	277.7	220.5	132.9	79.75	46.43	31.82	25.77	21.35	13.77	11.86	6.484
10.2V	396.3	266.7	217.6	131.7	79.16	46.14	31.70	25.56	21.14	13.67	11.75	6.365
10.5V	361.7	255.7	206.3	129.0	78.09	45.77	31.57	25.33	20.89	13.55	11.63	6.185
10.8V	326.3	239.2	194.9	126.0	76.81	45.39	31.20	25.23	20.68	13.49	11.45	5.825
11.1V	287.8	222.7	183.5	122.5	75.38	43.82	30.60	24.98	20.48	13.40	11.28	5.733

All mentioned values are average values.


# SCPV12-10 (12V20Ah)




Effect of temperature on long term float life




Storage characteristics



Charge characteristic Curve for standby use



Discharge characteristic Curve



Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	6V&12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%
	2V	60%	75%	85%	88%	92%	99%	100%	103%	105%	106%
AGM Battery	6V&12V	46%	66%	76%	83%	90%	98%	100%	103%	107%	109%
	2V	55%	70%	80%	85%	92%	99%	100%	104%	108%	110%

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/cell	1.75V	1.70V	1.60V
Discharge Current (A)	( A ) ≤ 0.2C	0.2C < ( A ) < 1.0C	( A ) ≥ 1.0C

Maintenance & Cautions

<b>Float Service:</b>
✘ Every month, recommend inspection every battery voltage.
✘ Every three months, recommend equalization charge for one time.
Equalization charge method:
Discharge: 100% rate capacity discharge.
Charge: Max. current 0.3CA, constant voltage 2.4-2.45V/Cell charge 24h.
✘ Effect of temperature on float charge voltage: -3mV/°C/Cell.
✘ Length of service life will be directly affected by the number of discharge cycles, depth of discharge, ambient temperature and charging voltage.

**Charge the batteries at least once every six months, if they are stored at 25°C.**

Charging Method:

Constant Voltage	-0.2Cx2h+2.4~2.45V/Cellx24h, Max. Current 0.3CA
Constant Current	-0.2Cx2h+0.1CAx12h
Fast	-0.2Cx2h+0.3CAx4.0h