



# SCPV - TEMPEST Inline Filter - 16A4SRM For 19" Rack

Silicon CPV's inline, TEMPEST filter has been designed for use within stringent TEMPEST environments and applications, where protection compliant to SDIP-29 and equipment hardening to SDIP-27 is required.

The product uses ultra-reliable self-healing capacitors, in all units to deliver optimum performance across the full frequency range and under all loading conditions.

The SCPV filter has been designed for use within unprotected power environments to ensure deployment and electrical installation is as quick and simple as possible.

The product has been designed to support current ratings of **16 Amps** under single phase operating voltage conditions.



## Description

- TEMPEST EMI SP & N filter providing performance to SDIP-27 B/C
- Insertion loss of 60dB from 100kHz to 1GHz
- 2m, 3 core shieled flex cable for input & output connectivity, 4 x BS1363 sockets outlets
- Designed to IT equipment safety standard EN 62368-1
- Fully 360° screened input cable to maintain red/black separation to filter
- Low Smoke Zero Halogen (LSZH) rated cabling for use in sensitive areas
- Self-healing metallised plastic film capacitors
- High common & differential mode insertion loss
- Improved low frequency performance
- Powder coated aluminium enclosure
- 16A designs of filter are downline tolerable to a personnel protection RCCD
- CE compliant
- Simple mechanical and electrical installation
- Filters comply with basic requirements of the EMC directive 2014/30/EU






# **Ratings and Characteristics**

Rated Voltage	230V AC 50/60Hz
Test Voltage (line-earth)	2250V DC
Test Voltage (line-Line)	1250V DC
Rated Current @50°C	16A
Earth Leakage Current	Less than 3.0mA
Max Temp Rise @Full Load	<35°C

Storage Temp Range	-25°C to 85°C
Operating Temp	-20°C to 50°C
Range	
Insertion Loss (50Ω	60dB, 100KHz - 1GHz
Asymmetric)	
Discharge Time	Less than 1s to below
	34V
Enclosure	Extruded aluminium
Finish	Powder coated

## **Dimensional Data**


# 19" Rack Mount



Product Height 60mm

mm

# **Performance Characteristics and Insertion Loss Curves**



# **Part No and Ordering Information**

Part No	Product Description
SCPV-TEMPEST-16A4SRM	19" Rack, 16A Single Phase, 4 x 13A
CP&F Part No: SCPVTEMPEST16A4SRM	Socket 230V Filter